DESULFURIZING AGENT, METHOD FOR DESULFURIZATION AND METHOD FOR PRODUCING HYDROGEN FOR FUEL BATTERY

Patent Number:

JP2001279257

Publication date:

2001-10-10

Inventor(s):

KATSUNO TAKASHI; MATSUDA SATOSHI; YOSHINAKA MASAHIRO; SAITO KAZUHITO

Applicant(s):

IDEMITSU KOSAN CO LTD

Requested Patent:

JP2001279257

Application

Number:

JP20000096352 20000331

Priority Number(s):

IPC Classification:

C10G29/04; B01D15/00; B01J20/06; B01J23/46; C01B3/40; C10G25/05; C10G53/08;

H01M8/06

EC Classification:

Equivalents:

Abstract

PROBLEM TO BE SOLVED: To obtain a desulfurizing agent which can efficiently remove sulfur contents in a petroleum-based hydrocarbon and has a long life, to provide a desulfurization method by which the sulfur contents in the hydrocarbon can efficiently be removed down to a low concentration, and to provide a method for producing hydrogen for fuel batteries.

SOLUTION: This desulfurizing agent for petroleum-based hydrocarbons, is characterized by comprising iron carried on a carrier. The method for desulfurization, is characterized by desulfurizing a petroleum-based hydrocarbon with the desulfurizing agent and, if necessary, further bringing the desulfurized hydrocarbon into contact with a second desulfurizing agent. The method for producing the hydrogen for fuel batteries, is characterized by bringing the petroleum-based hydrocarbon brought into contact with the second desulfurizing agent into contact with a steam reformation catalyst.

Data supplied from the esp@cenet database - I2

Line

(19)日本国特許庁(JP)

(12) 公開特許公報(A)

(11)特許出廢公開番号 特開2001-279257 (P2001-279257A)

(43)公開日 平成13年10月10日(2001.10.10)

h*(参考) 0017			
6040			
3066			
3069			
1029			
終頁に続く			
目1番1号			
地			
7			

(54) 【発明の名称】 脱硫剤、脱硫方法及び燃料電池用水素の製造方法

(57)【要約】

【課題】 石油系炭化水素中の硫黄分を効果的に除去することができ、かつ寿命の長い脱硫剤、該炭化水素中の硫黄分を低濃度まで効率よく除去する脱硫方法及び燃料電池用水素の製造方法を提供すること。

【解決手段】 担体に鉄を担持してなる石油系炭化水素 用脱硫剤、この脱硫剤を用いて、石油系炭化水素を脱硫 処理し、場合により、第二の脱硫剤と接触させる脱硫方 法、並びに上記第二の脱硫剤と接触させた石油系炭化水 素を、水蒸気改質触媒と接触させて燃料電池用水素を製 造する方法である。